

SANIRELEV 22

TWIN PUMP UNIT FOR DOMESTIC SEWAGE

- SINGLE PHASE PEDESTAL WITH SEPARATE LEVEL CONTROL
- THREE PHASE PEDESTAL WITH SEPARATE LEVEL CONTROLS

SINGLE AND THREE PHASE CONTROL PANEL



LARGE SEALED LID FOR EASY ACCESS

KNURLED NUTS

OPTIONAL DISCHARGE MANIFOLD (SEE ACCESSORIES)

DISCHARGE CONNECTIONS

100 mm INLET STUBS

CABLE DUCT CONNECTION

VOL 540 Ltrs

300 mm EXTENSION OPTION

1035 mm

810 mm

725 mm

Weight without Pump 30kg

RIGID TANK FOR BELOW OR OVERGROUND APPLICATIONS

REINFORCING RING

HIGH DENSITY POLYHENE TANK

BENCHED BASE TO PREVENT SOLIDS BUILDING UP

LIFTING POINT

FITTED OUT TO ACCEPT 2 x DW VOX or DW PUMP

2 PEDESTAL ARRANGEMENT

Pedestal Mounting



Free Standing

DW (channel)
DW VOX (vortex)
Double Mechanical Shaft Seal
Class F Insulation. IP68 Rated
50 mm Free Passage.

